




CUPINA
LED Pole-Top Light Fitting
Series 556... G2

Applications:
556... G2:
Residential areas, residential and side streets, low traffic areas, footpaths and cycle tracks etc.
556... R G2:
Promenades, public parks, pedestrian areas etc.
Design :
Roof and supporting section: Aluminium, powder-coated DB 702 .
Cover: PMMA, clear, cylindrical.
Electrical components: Wired ready for installation, disconnect plug-in connector to the mains connection terminal, cable retainer for connection cable, with LED module and ECG unit.
Light distribution: Asymmetrical wide beam or symmetrical circular beam (**R**).
Mounting system: 3 non-corrosive steel locking screws serve for fixation on straight poles Ø 76 mm. Adapter (**RZ 1**) for pole end Ø 60 mm (see accessories / spare parts).

Electrical design:
LED module: 4,000 K or 3,000 K, R_a > 70, service life L_{95} > 100,000 h, Zhaga compliant
ECG: 220-240 V, 50-60 Hz, Surge voltage resistance 10 kV, overload and short circuit protection.







Options:
– 2,200 K; light colour (**722**)
– 1,800 K; light colour (**518**)
– asymmetrical extremely wide beam (**RWX**), for illuminating cycle paths
– special painting in RAL colours
– protection class I (**SKI**)
– seawater-resistant version
– for connection to a central power supply system (**ZB**)
– variable adjustable luminous flux via APP (**NFC**)
– Ready for Lightmanagement System (**RFL**), only possible without ring mirror accessories
– dimming function via DALI-2 interface, compatible with LIMAS Line wired Light Management System (**DIMD**)
– power reduction with control phase (**LR**)
– power reduction without control phase (**LA**)
– constant luminous flux function (**CL**)
– with backside light shielding (**HA**)
– Inclination adjustment of the LED unit, for illuminating wide roads

Product highlights:

- **long-lasting, corrosion-resistant aluminium construction**
- **quick installation** thanks to **tool-free opening** of the lumimaire
- **tool-free replacement of** ECG and LED module
- **homogeneous illumination** due to the **Multi-Layer-Technology**
- **BlackEdition, ULOR=0 %** (Modifications with accessories influence the light distribution)
- versions dimmable to 10% with luminous fluxes up to 2,000 lm and with color temperature up to 3,000 K comply with **Dark Sky requirements**
- control gear and LED-module replaceable by qualified personnel on-site
- **future proof** by using standardised LED-modules (Zhaga) and long-term availability of spare parts



RFL

All CUPINA luminaires are also available in an RFL version and are therefore, thanks to their Zhaga Book 18-compliant base with D4i control gear, prepared for the subsequent use of a Light Management System.

Properties, limitations and details for controlling LED-light fittings:
See "Technical Supplement"

All data are correct at the time of printing. Actual technical data can be found under www.schuch.de.

All light fittings also available with connected cable (see accessories in the data sheet).

556... G2

IP54 | Wind load area A = 0,13m²

asymmetrical wide beam

colour temperature 4.000K (light colour 740)

Article No.	Type	Connected load [W]	Luminous flux [lm]	Luminous efficacy [lm/W]	Weight [kg] (without packingmaterial)
55600 0001	**556 0801 G2**	9	1.430	159	6,7
55600 0002	**556 0802 G2**	13	2.000	154	6,7
55600 0003	**556 0803 G2**	18	2.690	149	6,7
55600 0004	**556 1601 G2**	17	2.850	168	6,8
55600 0005	**556 1602 G2**	25	3.950	158	6,8
55600 0006	**556 1603 G2**	35	5.280	151	6,8

colour temperature 3.000K (light colour 730)

55600 0013	**556 0801 G2 730**	9	1.360	151	6,7
55600 0014	**556 0802 G2 730**	13	1.900	146	6,7
55600 0015	**556 0803 G2 730**	18	2.560	142	6,7
55600 0016	**556 1601 G2 730**	17	2.710	159	6,8
55600 0017	**556 1602 G2 730**	25	3.750	150	6,8
55600 0018	**556 1603 G2 730**	35	5.020	143	6,8

symmetrical circular beam

colour temperature 4.000K (light colour 740)

55600 0007	**556 0801R G2**	9	1.430	159	6,7
55600 0008	**556 0802R G2**	13	2.000	154	6,7
55600 0009	**556 0803R G2**	18	2.690	149	6,7
55600 0010	**556 1601R G2**	17	2.850	168	6,8
55600 0011	**556 1602R G2**	25	3.950	158	6,8
55600 0012	**556 1603R G2**	35	5.280	151	6,8

colour temperature 3.000K (light colour 730)

55600 0019	**556 0801R G2 730**	9	1.360	151	6,7
55600 0020	**556 0802R G2 730**	13	1.900	146	6,7
55600 0021	**556 0803R G2 730**	18	2.560	142	6,7
55600 0022	**556 1601R G2 730**	17	2.710	159	6,8
55600 0023	**556 1602R G2 730**	25	3.750	150	6,8
55600 0024	**556 1603R G2 730**	35	5.020	143	6,8



All light fittings also available with connected cable (see accessories in the data sheet).

All luminaires also available with luminous flux adjustment via app (**NFC version**).

Article No.	Type	Connected load [W]	Luminous flux [lm] 1)	Luminous efficacy [lm/W] (up to)	Substitute for ca. *	Weight [kg] (without packing material)

556... G2 VARIO

IP54 | Wind load area A = 0,13m²

Design:
Same as type 556... G2 but: With an integrated DIP switch for for variable adjustment of the luminous flux in the luminaire.

Product highlights of the VARIO version:

- **simple, fast, tool-free setting of the luminous flux** on site, by means of integrated switch, can be changed at any time
- **reduction in the variety of types**

asymmetrical wide beam

colour temperature 3.000K (light colour 730)

55601 0002	**556 L25 G2 VARIO**	5 - 18	660 - 2.690	144	HST 35 - HST 50	6,7
55601 0003	**556 L50 G2 VARIO**	9 - 35	1.320 - 5.280	156	HST 35 - 2 x HST 70	6,8

colour temperature 3.000K (light colour 730)

55601 0004	**556 L25 G2 VARIO 730**	5 - 18	630 - 2.560	136	HST 35 - HST 50	6,7
55601 0005	**556 L50 G2 VARIO 730**	9 - 35	1.250 - 5.020	147	HST 35 - 2 x HST 70	6,8

symmetrical circular beam

colour temperature 4.000K (light colour 740)

55601 0006	**556 L25R G2 VARIO**	5 - 18	660 - 2.690	144	HST 35 - HST 50	6,7
55601 0007	**556 L50R G2 VARIO**	9 - 35	1.320 - 5.280	156	HST 35 - 2 x HST 70	6,8

colour temperature 3.000K (light colour 730)

55601 0008	**556 L25R G2 VARIO 730**	5 - 18	630 - 2.560	136	HST 35 - HST 50	6,7
55601 0009	**556 L50R G2 VARIO 730**	9 - 35	1.250 - 5.020	147	HST 35 - 2 x HST 70	6,8

Factory setting L25: 18 W; replaces approx. HME 80, HST 50

Factory setting L50: 18 W; replaces approx. HME 125, HST 70

1) possible setting range

* The given information is for rough orientation only. In each individual case a lighting calculation is necessary.



with ring mirror



with frosted board cover



with frosted board cover and ring mirror



Accessories / Spare Parts

Article no.	Type	
10051 9000	**ABD 541/55. G2 PMMA**	cover, cylinder PMMA clear, for 541, 553, 556, 557, 558...
10041 9001	**ABDP 54./55. C PMMA**	board cover, diffuser for glare limitation, diffuser PMMA satined, for 541, 543, 553, 556, 557, 558…
90116 9004	**RS 54./55. G2**	ring mirror, aluminium for series 541, 543, 553, 556, 557, 558… (Design element)
90126 0001	**RZ 1 BK**	adapter for mast top Ø 60 mm