

 MADE IN GERMANY

**BEST
SELECT** 



BestSelect

Strong on price. Strong on performance.

Top quality meets unbeatable price-performance ratio.

 **SCHUCH**

BEST SELECT.

The lighting range for your everyday life.

BestSelect is a selection of tried-and-tested SCHUCH luminaires for your everyday needs. They impress with their unbeatable price-performance ratio, top efficiency and very long service life, and are readily available. This puts them at a clear ad-

vantage in terms of the cost-effectiveness and sustainability of investments.

Save time, reduce costs and choose SCHUCH quality. Your customers will appreciate it.

LUXANO 2 VARIO

CAMINO VARIO

FILOS VARIO

TRIANO disc



ELIGIBLE

NO DISPOSABLE LUMINAIRES

REPAIRABLE

5-YEAR GUARANTEE

SUSTAINABLE

AVAILABLE QUICKLY

NO DISPOSABLE LUMINAIRES

REPAIRABLE

SUSTAINABLE

REPAIRABLE

5-YEAR GUARANTEE

ELIGIBLE

SUSTAINABLE

AVAILABLE QUICKLY

5-YEAR GUARANTEE

AVAILABLE QUICKLY

NO DISPOSABLE LUMINAIRES

LUXANO 2 VARIO

Simply ingenious and versatile

The inexpensive LUXANO 2 damp-proof luminaire impresses with its durability, comparatively high efficiency and versatility. A single luminaire type can replace conventional types ranging from 1x36 W to 2x58 W, offering extreme economy and flexibility while enabling maximum standardisation and optimal warehousing. High-speed installation? No problem with the fully pre-assembled FC version.

ADVANTAGES AT A GLANCE

- variable luminous flux adjustable on site tool-free
- top quality and highly efficient
- FastFix quick mounting system
- variable cable entries, closed knock-outs on the short and long sides, and on the backside
- service life L80 > 70,000 h

Article no.	Type	Connected load [W]	Luminous flux [lm] ¹	Luminous efficacy [lm/W]	Substitute for
16700 0020	167 12LG2 VARIO	18 – 30	2,700 – 4,300	143 – 150	1 x 36 W – 2 x 36W
16700 0021	167 15LG2 VARIO	25 – 43	3,800 – 6,200	144 – 152	1 x 58 W – 2 x 58W

¹ possible setting range.

Rounded values, technical developments reserved.



Product details





Product details



CAMINO VARIO

Streets in perfect light

The CAMINO is the perfect solution when you need that little bit extra: greater convenience during installation thanks to its two-piece die-cast aluminium housing, greater sustainability thanks to its GreenLine label, and a little more style thanks to its smooth surface without cooling fins.

ADVANTAGES AT A GLANCE

- variably adjustable luminous flux – simple, quick, tool-free
- time- and cost-saving mounting thanks to removable upper part of the housing
- universal pole mounting system, foldabel without tool
- high system service life L90 > 100.000 h and high efficient
- eco-friendly, ULOR = 0



FILOS VARIO

It couldn't be more universal

Variability that gives you flexibility – that's what makes FILOS VARIO stand out. With its variably adjustable luminous flux, it covers a wide range of applications, either with a lightweight glass fibre reinforced polyester housing (unpainted or painted) or as a GreenLine version with a die-cast aluminium housing. Always the right luminaire at hand!

ADVANTAGES AT A GLANCE

- variably adjustable luminous flux – simple, quick, tool-free
- easy to install: tool-free opening, detachable gear tray, integrated universal pole mounting system, multi-function cable entry
- highly efficient up to 185 lm/W
- high system service life L90 > 100.000 h
- eco-friendly, ULOR = 0 %

Article no.	Type	Colour	Connected load [W]	Luminous flux [lm] ¹	Luminous efficacy [lm/W]	Substitute for
42008 0001	42 L50 VARIO	Light grey RAL 7035	9 – 35	1,400 – 5,670	181	HST 35 – 2 x HST 70
42008 0002	42 L50 VARIO 730	Light grey RAL 7035	9 – 35	1,330 – 5,390	172	HST 35 – 2 x HST 70
42008 0501	42 L50 VARIO DB702	Mica-iron DB702	9 – 35	1,400 – 5,670	181	HST 35 – 2 x HST 70
42008 0502	42 L50 VARIO 730 DB702	Mica-iron DB702	9 – 35	1,330 – 5,390	172	HST 35 – 2 x HST 70

¹ possible setting range.

Rounded values, technical developments reserved.



Product details

Article no.	Type	Connected load [W]	Luminous flux [lm] ¹	Luminous efficacy [lm/W]	Substitute for
48001 0703	48 L50 VARIO	9 – 35	1,400 – 5,670	173	HST 35 – 2 x HST 70
48001 0701	48 L50 VARIO 730	9 – 35	1,330 – 5,480	163	HST 35 – 2 x HST 70
48001 0750	48 L100 VARIO	16 – 50	2,730 – 11,140	177	HST 50 – HME 250
48001 0761	48 L100 VARIO 730	16 – 50	2,590 – 10,580	168	HST 50 – HME 250
48700 0002	4871 RAL 7035	Welded Aluminium Pole Arm Carrier for mounting outdoor light fittings on flat walls and corners of buildings.			
48700 0506	4871 DB702				

¹ possible setting range.

Rounded values, technical developments reserved.





Product details



TRIANO disc

There is no alternative to quality

Striking, unmistakable design and the best SCHUCH quality „Made in Germany“ – that’s what the TRIANO disc series of high-bay luminaires is all about. They are available in three sizes, offering the perfect solution for any hall and also scoring points for their ease of installation and short payback period.

ADVANTAGES AT A GLANCE

- long-lasting, corrosion-resistant die-cast aluminium housing with cooling fin structure
- high system service life L80 > 100,000 h
- high energy cost savings thanks to low connected load and high efficiency
- fast mounting and commissioning due to 1-point suspension and FastConnect quick-connector



Article no.	Type	Connected load [W]	Luminous flux [lm]	Luminous efficacy [lm/W]	Colour temperature [K]	Substitute for
34100 0003	3410 L100B D	65	10,000	154	5,000	HME250
34200 0003	3420 L200B D	123	20,000	163	5,000	HIT250 / HME400
34200 0005	3420 L200TB D	123	20,000	163	5,000	HIT250 / HME400
34300 0003	3430 L300B D	195	30,000	154	5,000	HIT400
34300 0005	3430 L300TB D	195	30,000	154	5,000	HIT400
34100 0011	3410 L100B D 840	65	10,000	154	4,000	HME250
34200 0011	3420 L200B D 840	123	20,000	163	4,000	HIT250 / HME400
34200 0015	3420 L200TB D 840	123	20,000	163	4,000	HIT250 / HME400
34300 0014	3430 L300B D 840	195	30,000	154	4,000	HIT400
34300 0017	3430 L300TB D 840	195	30,000	154	4,000	HIT400

Rounded values, technical developments reserved.



LUXANO 2 VARIO

Article no.	Type	Connected load [W]	Luminous flux [lm] ¹	Luminous efficacy [lm/W]	Substitute for
16700 0020	167 12LG2 VARIO	18 – 30	2.700 – 4.300	143 – 150	1 x 36 W – 2 x 36 W
16700 0021	167 15LG2 VARIO	25 – 43	3.800 – 6.200	144 – 152	1 x 58 W – 2 x 58 W

Also available as a fully pre-assembled FC version.

FILOS VARIO

Article no.	Type	Colour	Connected load [W]	Luminous flux [lm] ¹	Luminous efficacy [lm/W]	Substitute for
42008 0001	42 L50 VARIO	Lichtgrau RAL 7035	9 – 35	1.400 – 5.670	181	HST 35 – 2 x HST 70
42008 0002	42 L50 VARIO 730	Lichtgrau RAL 7035	9 – 35	1.330 – 5.390	172	HST 35 – 2 x HST 70
42008 0501	42 L50 VARIO DB702	Eisenglimmer DB702	9 – 35	1.400 – 5.670	181	HST 35 – 2 x HST 70
42008 0502	42 L50 VARIO 730 DB702	Eisenglimmer DB702	9 – 35	2.330 – 5.390	172	HST 35 – 2 x HST 70

Also available with die-cast aluminium housing.

CAMINO VARIO

Article no.	Type	Connected load [W]	Luminous flux [lm] ¹	Luminous efficacy [lm/W]	Substitute for
48001 0703	48 L50 VARIO	9 – 35	1.330 – 5.480	172	HST 35 – 2 x HST 70
48001 0701	48 L50 VARIO 730	9 – 35	1.260 – 5.210	163	HST 35 – 2 x HST 70
48001 0750	48 L100 VARIO	16 – 50	2.730 – 11.140	177	HST 50 – HME 250
48001 0761	48 L100 VARIO 730	16 – 50	2.590 – 10.580	168	HST 50 – HME 250
48700 0002	4871 RAL 7035	Welded Aluminium Pole Arm Carrier for mounting outdoor light fittings on flat walls and corners of buildings.			
48700 0506	4871 DB702				

TRIANO disc

Article no.	Type	Connected load [W]	Luminous flux [lm]	Luminous efficacy [lm/W]	Colour temperature [K]	Substitute for
34100 0003	3410 L100B D	65	10,000	154	5,000	HME250
34200 0003	3420 L200B D	123	20,000	163	5,000	HIT250 / HME400
34200 0005	3420 L200TB D	123	20,000	163	5,000	HIT250 / HME400
34300 0003	3430 L300B D	195	30,000	154	5,000	HIT400
34300 0005	3430 L300TB D	195	30,000	154	5,000	HIT400
34100 0011	3410 L100B D 840	65	10,000	154	4,000	HME250
34200 0011	3420 L200B D 840	123	20,000	163	4,000	HIT250 / HME400
34200 0015	3420 L200TB D 840	123	20,000	163	4,000	HIT250 / HME400
34300 0014	3430 L300B D 840	195	30,000	154	4,000	HIT400
34300 0017	3430 L300TB D 840	195	30,000	154	4,000	HIT400

Rounded values, technical developments reserved.

Follow us:



... with passion for excellent lighting!

